

BEST AVAILABLE COPY

MAR 20 2006 10:26 FR HAS - CONCORD

603 224 8350 TO 15712738300

P.07/13

U.S. Pat. App. Ser. No. 10/720,368
Docket No. 05665.50120421
Amendment and response to 11/29/2005 Office Action

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Cancelled)
2. (Currently amended) The valve of claim 3 4, wherein the safety valve and screw cap are permanently joined integrally connected.
3. (Currently amended) The valve of claim 1, wherein the safety valve comprises: A valve comprising, in combination:
a valve cup having a fill hole;
a screw cap; and
a safety valve, removably insertable into the fill hole to function as a stopper for
the fill hole, comprising:
a stopper portion having a check valve; and
a safety cap that is removably insertable into the stopper portion.
4. (Original) The valve of claim 3, wherein the safety valve further comprises a seal portion.
5. (Cancelled)
6. (Currently amended) The valve of claim 2 5, wherein the safety valve further comprises a seal portion.
7. (Currently amended) The valve of claim 3 4, wherein the cap has exterior grooves.
8. (Original) The valve of claim 3, wherein the safety cap is attached to the stopper portion by a flexible stem.

BEST AVAILABLE COPY

MAR 23 2006 10:26 FR HAS - CONCORD

603 224 8350 TO 15712738300

P.08/13

U.S. Pat. App. Ser. No. 10/720,318
Docket No. 056655/01/30421
Amendment and response to 11/29/2005 Office Action

9. (Currently amended) The valve of claim 3, the safety cap valve further comprising a safety cap release valve tab.

10. (Cancelled)

11. (Currently amended) The valve of claim 12 10, wherein the cap is permanently joined integrally connected to the stopper.

12. (Currently amended) The valve of claim 10, wherein the stopper portion has A valve comprising, in combination:

a valve cup, the valve cup having a valve chassis surrounding a fill valve hole;
a stopper, the stopper being removably inserted into the fill valve hole and
comprising a safety valve, the safety valve comprising;

a check valve; and
the safety valve has a safety cap that is removably insertable into the
stopper portion; and
a cap, the cap being removably screwable onto the valve chassis to secure the
stopper in the fill valve hole and having a hole through which the safety valve is accessed.

13. (Currently amended) The valve of claim 12 10, wherein the stopper further comprises a seal portion.

14. (Currently amended) The valve of claim 12, wherein the safety cap is attached to the stopper portion by a flexible stem.

15. (Cancelled)

16. (Currently amended) The valve of claim 17 15, wherein the cap is permanently joined integrally connected to the safety valve.

BEST AVAILABLE COPY

MAR 23 2006 10:26 FR HAS - CONCORD

603 224 8350 TO 15712738300

P.09/13

U.S. Pat. App. Ser. No. 11/0720,368
Docket No. 056655/0120421
Amendment and response to 11/0720,368 Office Action

17. (Currently amended) The valve of claim 15, wherein the safety valve further comprises: A valve comprising, in combination:

a safety valve; the safety valve incorporating a stopper portion and comprising:

a check valve; and

a safety cap that is removably insertable into the stopper portion;

a valve cup, the valve cup adapted for receiving the stopper portion of the safety valve into a fill valve hole; and

a cap, the cap adapted for securing the safety valve into the fill valve hole.

18. (Currently amended) The valve of claim 17-15, wherein the safety valve further comprises a seal portion.

19. (Original) The valve of claim 17, wherein the safety cap is attached to the stopper portion by a flexible stem.

20. (Cancelled)